



Product Data Sheet

Aminol™ Hydraulic WR HLP 150

Hydraulic oil

Product description

Aminol™ Hydraulic WR HLP 150 is a premium-grade hydraulic oil blended with highly refined base oils and an advanced additive package. Its formulation exhibits enhanced features, including superior antioxidant, anti-corrosive, anti-wear, anti-foam, and viscosity properties.

Application

Aminol™ Hydraulic WR HLP 150 is recommended for application in the hydraulic systems of industrial equipment that operate under rigorous mechanical and thermal demands. It is particularly well-suited for deployment in conditions of severe waterlogging, ensuring optimal performance and reliability.

Features & Benefits

- Minimizes equipment wear.
- Extends service life.
- Exhibits excellent anti-foam properties.
- Improves air separation.
- Well-suited for use in heavily watered systems.

Typical Properties

Property	Unit	Test method	Typical value
ISO viscosity grade	-	-	150
Density at 15°C	g/cm ³	ASTM D4052	0.890
Kinematic Viscosity at 40°C	mm ² /s	ASTM D445	150.0
Kinematic Viscosity at 100°C	mm ² /s	ASTM D445	14.61
Viscosity Index	-	ASTM D2270	95
Flash Point (COC)	°C	ASTM D92	230
Pour Point	°C	ASTM D97	-15
Water separability	min	ASTM D7451	15



-time to 3 ml emulsion min	min	ASTM D7451	15
Oxidation Stability after 1000h/TAN increase	min	ASTM D4310	<1.5
FZG EP Wear Test (A 8.3/90)	-	ASTM D 5182	11
Failure Load Stage	-	ASTM D 5182	11

Typical property characteristics are based on current production. Whilst future production will conform to Aminol™ specifications, variations in these characteristics may occur.

Performance claims

- DIN 51524-2 (HLP)
- Sulzer
- KraussMaffei

Health, Safety & Environment

- **Health and Safety**

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application, and good standards of industrial and personal hygiene are maintained.

For further guidance on Product Health & Safety refer to the appropriate Safety Data Sheet which can be obtained upon request or through our website: www.aminol.az

- **Protect the Environment**

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

Available pack sizes

- 1 L Canister plastic
- 4 L Canister plastic
- 5 L Canister plastic
- 7 L Canister plastic
- 20 L Canister plastic
- 30 L Canister plastic
- 200 L Drum sheet metal
- 1000 L Container

Storage

- We recommend to store all packages under cover.
- Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings.
- Products should not be stored above 60 °C, exposed to hot sun or freezing conditions.



Notes

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by ALCO LLC for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our sales specialists if you require any further information.