



Product Data Sheet

Aminol™ Hydraulic Xtreme 32 ULT

Hydraulic oil

Product description

Aminol™ Hydraulic Xtreme 32 ULT is an advanced hydraulic fluid designed for applications subjected to extremely low ambient temperatures, such as Arctic or exposed areas. It consistently delivers high performance even in environments with widely fluctuating temperatures, making it ideal for use in industrial and mobile hydraulic systems operating under heavy load conditions.

Application

- Mobile and industrial equipment operating at extremely low temperatures
- Hydraulic systems operating at high pressures and under heavy operating conditions
- Vehicles, agricultural, construction, and mining equipment operating in extremely cold environments
- Hydraulic servo equipment
- Circulation systems

Features & Benefits

- Exceptional anti-wear protection
- Outstanding oxidation and thermal stability
- Excellent water separability and hydrolytic stability
- Great foam and air release performance
- Improved rust and corrosion protection

Typical Properties

Property	Unit	Test method	Typical value
ISO viscosity grade	-	-	32
Density at 15°C	g/cm ³	ASTM D4052	0.831
Kinematic Viscosity at 40°C	mm ² /s	ASTM D445	32.00
Kinematic Viscosity at 100°C	mm ² /s	ASTM D445	9.440
Viscosity Index	-	ASTM D2270	300
Flash Point (COC)	°C	ASTM D92	150
Pour Point	°C	ASTM D97	-60



Typical property characteristics are based on current production. Whilst future production will conform to Aminol™ specifications, variations in these characteristics may occur.

Performance claims

- DIN 51524-3 (HVLP)
- ISO-L-HV

Health, Safety & Environment

- **Health and Safety**

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application, and good standards of industrial and personal hygiene are maintained.

For further guidance on Product Health & Safety refer to the appropriate Safety Data Sheet which can be obtained upon request or through our website: www.aminol.az

- **Protect the Environment**

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

Available pack sizes

- 1 L Canister plastic
- 4 L Canister plastic
- 5 L Canister plastic
- 7 L Canister plastic
- 20 L Canister plastic
- 30 L Canister plastic
- 200 L Drum sheet metal
- 1000 L Container

Storage

- We recommend to store all packages under cover.
- Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings.
- Products should not be stored above 60 °C, exposed to hot sun or freezing conditions.



Notes

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by ALCO LLC for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our sales specialists if you require any further information.