



Product Data Sheet

Aminol™ MaxPro 5W-40 SP

Engine oil

Product description

Aminol™ MaxPro 5W-40 SP is a universal, high-performance fuel-saving engine oil engineered for the latest gasoline and diesel engine technologies, providing excellent all-round performance. Formulated with carefully selected base stocks and unique additive technology, it delivers exceptional wear protection and engine cleanliness

Application

Aminol™ MaxPro 5W-40 SP is suitable for use in automotive petrol and diesel vehicles where the manufacturer recommends an ACEA A3/B4, API SP or earlier specification 5W-40 lubricant.

Features & Benefits

- Excellent fluidity at low temperature.
- Lower fuel consumption and CO2 emissions.
- Outstanding engine cleanliness and durability.
- Long drain interval
- Reduced power-robbing friction across engine speeds and conditions

Typical Properties

Property	Unit	Test method	Typical value
Kinematic Viscosity at 100°C	cst	ASTM D 445	14.5
Kinematic Viscosity at 40°C	cst	ASTM D 445	94.4
Viscosity Index	-	ASTM D 2270	160
Flash Point, COC	°C	ASTM D 92	228
Pour Point	°C	ASTM D 97	-39
TBN	mg KOH/g	ASTM D 2896	10.2
Sulphated Ash Content	%	ASTM D 874	1.3
Density at 15°C	g/ml	ASTM D 4052	0.84



Typical property characteristics are based on current production. Whilst future production will conform to Aminol™ specifications, variations in these characteristics may occur.

Performance claims

- API SP
- ACEA A3/B4

ALCO LLC recommends this product for vehicles with the following specifications:

- MB 229.3/229.5
- VW 502.00/505.00
- Renault RN 0700/0710
- PSA B71 2296

Health, Safety & Environment

- **Health and Safety**

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application, and good standards of industrial and personal hygiene are maintained.

For further guidance on Product Health & Safety refer to the appropriate Safety Data Sheet which can be obtained upon request or through our website: www.aminol.az

- **Protect the Environment**

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

Available pack sizes

- 1 L Canister plastic
- 4 L Canister plastic
- 5 L Canister plastic
- 7 L Canister plastic
- 20 L Canister plastic
- 30 L Canister plastic
- 200 L Drum sheet metal
- 1000 L Container

Storage

- We recommend to store all packages under cover.
- Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings.
- Products should not be stored above 60 °C, exposed to hot sun or freezing conditions.



Notes

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by ALCO LLC for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our sales specialists if you require any further information.