



# Product Data Sheet

## Aminol™ ProTech 0W-30 SN A5/B5

Engine oil

### Product description

Aminol™ ProTech 0W-30 SN A5/B5 is a high-quality, fuel-saving multigrade motor oil manufactured through the latest technology. It has specially been designed to enhance and protect the efficiency of exhaust emission reduction systems in new-generation passenger and light commercial vehicles powered by diesel or gasoline engines.

### Application

Aminol™ ProTech 0W-30 SN A5/B5 is recommended for year-round usage in modern gasoline and diesel engines with direct fuel injection, operated in extreme conditions.

### Features & Benefits

- Unmatched sludge protection
- Low viscosity and friction characteristics
- Exceptional wear and corrosion protection
- Facilitates easier cold starting
- Ensures engine protection throughout the drain interval, even under extreme pressure
- High fuel efficiency and performs well in low temperatures

### Typical Properties

Property	Unit	Test method	Typical value
Kinematic Viscosity at 100°C	cst	ASTM D 445	10.5
Kinematic Viscosity at 40°C	cst	ASTM D 445	58.5
Viscosity Index	-	ASTM D 2270	172
Flash Point, COC	°C	ASTM D 92	218
Pour Point	°C	ASTM D 97	-42
TBN	mg KOH/g	ASTM D 2896	10.2
Sulphated Ash Content	%	ASTM D 874	1.3
Density at 15°C	g/ml	ASTM D 4052	0.845



Typical property characteristics are based on current production. Whilst future production will conform to Aminol™ specifications, variations in these characteristics may occur.

### Performance claims

- API SN
- ACEA A5/B5

**ALCO LLC recommends this product for vehicles with the following specifications:**

- ILSAC GF2
- Volvo 95200377

### Health, Safety & Environment

- **Health and Safety**

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application, and good standards of industrial and personal hygiene are maintained.

For further guidance on Product Health & Safety refer to the appropriate Safety Data Sheet which can be obtained upon request or through our website: [www.aminol.az](http://www.aminol.az)

- **Protect the Environment**

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

### Available pack sizes

- 1 L Canister plastic
- 4 L Canister plastic
- 5 L Canister plastic
- 7 L Canister plastic
- 20 L Canister plastic
- 30 L Canister plastic
- 200 L Drum sheet metal
- 1000 L Container

### Storage

- We recommend to store all packages under cover.
- Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings.
- Products should not be stored above 60 °C, exposed to hot sun or freezing conditions.



## Notes

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by ALCO LLC for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our sales specialists if you require any further information.