



# Product Data Sheet

## Aminol™ GearSynth 68

Industrial gear oil

### Product description

Aminol™ GearSynth 68 is a fully synthetic, premium-performance, extreme-pressure lubricant specifically designed for enclosed industrial gears and bearings that operate under severe load conditions and extreme temperatures. Formulated using synthetic PAO base oils and specially selected additive technologies, it provides excellent protection against corrosion, wear, micropitting, and offers an extended oil service life due to its exceptional thermal stability

### Application

Aminol™ GearSynth 68 is suitable for application in industrial transmissions, where roller and plain bearings are subjected to high pressure and also for large-scale plants with pressure-feed lubrication systems.

### Features & Benefits

- Long drain intervals
- Exceptional film strength and extreme pressure resistance
- Robust protection against rust and corrosion
- Extended equipment life
- Effective water separation and demulsification characteristics
- Low foaming tendency

### Typical Properties

Property	Unit	Test method	Typical value
ISO viscosity grade	-	-	68
Density at 15°C	g/cm <sup>3</sup>	ASTM D 4052	0.829
Kinematic Viscosity at 40°C	mm <sup>2</sup> /s	ASTM D 445	68.00
Kinematic Viscosity at 100°C	mm <sup>2</sup> /s	ASTM D445	11.34
Viscosity Index	-	ASTM D 2270	160
Flash Point (COC)	°C	ASTM D 92	236
Pour Point	°C	ASTM D 97	-42
Copper Strip Corrosion	-	ASTM D 130	1b



Typical property characteristics are based on current production. Whilst future production will conform to Aminol™ specifications, variations in these characteristics may occur.

### Performance claims

- AIST 224
- AGMA 9005-F16-AS
- DIN51517-3 (CLP)
- ISO 12925-1 Type CKD
- FAG
- SKF

### Health, Safety & Environment

- **Health and Safety**

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application, and good standards of industrial and personal hygiene are maintained.

For further guidance on Product Health & Safety refer to the appropriate Safety Data Sheet which can be obtained upon request or through our website: [www.aminol.az](http://www.aminol.az)

- **Protect the Environment**

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

### Available pack sizes

- 1 L Canister plastic
- 4 L Canister plastic
- 5 L Canister plastic
- 7 L Canister plastic
- 20 L Canister plastic
- 30 L Canister plastic
- 200 L Drum sheet metal
- 1000 L Container

### Storage

- We recommend to store all packages under cover.
- Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings.
- Products should not be stored above 60 °C, exposed to hot sun or freezing conditions.



## Notes

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by ALCO LLC for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our sales specialists if you require any further information.